

TEST LEADS

UT-L Series

UT-L01 Tweezers test leads

- Length: 450mm, Probe length: 5mm
- Safety level: CAT III 1000V
- Application: SMT components measurement, universal test leads
- Amount: 1PC



UT-L02 BNC alligator clip test leads

- Length: 1000mm, Clip opening: 3mm
- Safety level: CAT II 600V 2A
- Application: BNC connector for instrument inputs
- Amount: 1PC



UT-L06 Dual head connectors

- Length: test leads 1200mm
- Safety level: CAT III 1000V 10A
- Application: Multifunctional connectors, all multimeters and clamps
- Amount: 1 pair



UT-L07 Probes

- Length: 1000mm, Probe length: 5mm+12mm
- Temperature condition: -15°C-40°C
- Safety level: CAT III 1000V 10A
- Features and application: Double insulated, lantern probes, removable probe protector, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



UT-L09 Dual head connectors

- Length: 1000mm, one head is 180°, the other is 90°
- Temperature condition: -15°C-40°C
- Safety level: CAT III 1000V 10A
- Features and application: Double insulated, banana plug with security mask and standard diameter, suitable for multiple devices, all multimeters and clamps
- Amount: 1 pair



UT-L10 Dual head multifunctional connectors

- Length: 1000mm, ø4mm
- Temperature condition: -15°C-40°C
- Safety level: CAT III 1000V 10A
- Features and application: Banana plug, used for testing adapter cables
- Amount: 1 pair



UT-L13 Probes

- Leads length: 1200mm, Rod length: 128mm
- Tip length: 18mm, with 44mm standard lantern tip
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Temperature condition: -15°C-40°C
- Features and application: Double insulated UL authenticated material, 44mm standard lantern-tip probe, which can be connected to standard alligator clips and test leads, removable tip shield sleeve, general type probes
- Amount: 1 pair



UT-L16 Probes

- Length: 1200mm, Rod length: 133mm
- Tip length: 18mm
- Safety level: CAT III 1000V 16A
- Safety certificate: EN 61010-031:2015
- Features and application: Double insulated silicone wire material, through hole type input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



UT-L17 Probe with LED light

- leads length: 1000mm
- Tip length: 16mm
- Safety level: CAT II 1000V 10A
- Features and application: Controllable LED light source, all multimeters and clamps measuring within spec
- Amount: 1PC



UT-L20 Probes

- Leads length: 900mm, Rod length: 101mm
- Tip length: 16.5mm
- Safety level: CAT I 1000V/CAT II 600V 10A
- Features and application: Cross plug with shield sleeve, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



UT-L21 Probes

- Leads length: 900mm, Rod length: 133mm
- Tip length: 15.8mm
- Safety level: CAT III 1000V/CAT IV 600V 20A
- Features and application: Cross plug with shield sleeve, general type probes, all multimeters and clamps
- Amount: 1 pair



UT-L25 Probes

- Leads length: 900mm, Rod length: 115mm
- Tip length: 18mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated wire, removable tip shield sleeve, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



TEST LEADS

UT-L Series

UT-L26 Probes

- Leads length: 900mm, Rod length: 136mm
- Tip length: 15.7mm
- Safety level: CAT III 1000V/CAT IV 600V 20A
- Safety certificate: EN 61010-031 2015
- Features and application: UL 16AWG double insulated wire, removable tip shield sleeve, cross type input terminal with full protection, general type probes, all multimeters and clamps
- Amount: 1 pair



UT-L27 Probes

- Leads length: 900mm, Rod length: 130mm
- Tip length: 16.3mm, threaded
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated UL authenticated material, removable tip shield sleeve, banana plug input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair




UT-L28 Probes

- Leads length: 900mm, Rod length: 128mm
- Tip length: 16.8mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Features and application: Double insulated wire, removable tip shield sleeve, banana plug input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



UT-L29 Probes

- Leads length: 900mm, Rod length: 136mm
- Tip length: 15.7mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated UL authenticated material, through hole crosshead with full protection input, removable tip shield sleeve, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



UT-L30 Probes

- Leads length: 900mm, Rod length: 136mm
- Tip length: 15.7mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated UL authenticated material, removable tip shield sleeve, cross input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



UT-L29 Probes

- Leads length: 900mm, Rod length: 136mm
- Tip length: 15.7mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated UL authenticated material, through hole crosshead with full protection input, removable tip shield sleeve, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



UT-L30 Probes

- Leads length: 900mm, Rod length: 136mm
- Tip length: 15.7mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031 2015
- Features and application: Double insulated UL authenticated material, removable tip shield sleeve, cross input terminal, general type probes, all multimeters and clamps measuring within spec
- Amount: 1 pair



UT-L31 Probes

- Line length: 1300mm
- Tip length: 18.5mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Features and application: rod with switch, removable tip shield sleeve, used for UT505B
- Amount: 1PC



UT-L32 Group test leads

- Combinations: combined with 2PCS test leads, (red+black) and (yellow+blue)
- Material: Double insulated leads
- Line length: 1090mm
- Safety level: CAT III 600V/CAT IV 300V
- Application: UT243
- Amount: 1 Group



UT-L33 Group test leads

- Combinations: combined with 1PCS (red+black) alligator clip test leads and 1PCS double-plug alligator clip test leads
- Material: Double insulated UL authenticated material
- Total length: 1200±20mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Application: UT511
- Amount: 1 Group



UT-L35 Group test leads

- Combination: (1) 1.6m test lead (green+red) 1pair (2) 5m green test lead 1PCS (3) 10m yellow test lead 1PCS (4) 20m red test lead 1PCS
- Material: UL authenticated material
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Application: UT521, UT522, UT572
- Amount: 1 Group

