

iENV ienv app





Main features

- 1. Wireless data transfer through Bluetooth
- 2. Real-time data and trends display

Mini Environmental BT Series

- 3. Real-time/historical/off-line data and trends recall. Data export in csv, pdf, or graphical format files that can be sent through E-mail
- 4. Attach pictures taken with phone into data reports
- 5. Allows user and company info to be filled in with reports and able to send reports through email
- 6. Bluetooth connectivity distance is roughly 10 meters in open space



Alert

UT333/UT333BT

Mini Temperature Humidity Meters

UT333/UT333BT temperature humidity meters can measure, process data, and display results on LCD. UT333BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and data export. iENV can be downloaded from Google Play, Apple Store or UNI-T's website by searching 'iENV'.

MAX/MIN	● °C/°F selection
● Data hold	LCD backlight

SPECIFICATION	UT333	UT333BT	
Certificates	CE, RoHS		
Temperature range	-10°C~60°C/14°F~140°F	-10°C~60°C/14°F~140°F	
Temperature accuracy	±1°C/±2°F	±1°C/±2°F	
Temperature resolution	0.1°C/0.2°F	0.1°C/0.2°F	
Humidity range	0%RH~100%RH	0%RH~100%RH	
Humidity accuracy	±5%RH	±5%RH	
Humidity resolution	0.1%RH	0.1%RH	
Sampling rate	1/s	1/s	
Bluetooth APP		√	
Overload indication	√	V	
Auto power off	5 min	5 min	
Low battery indication	3V~3.5V	3V~3.5V	
GENERAL CHARACTERISTICS			
Power	1.5V battery (R03) x 3		
Display	32mm x 26mm		
Product net weight	102g		
Product size	155mm x 50mm x 28mm		
Standard accessories	Batteries, English manual		
Standard individual packing	Blister		
Standard quantity per carton	UT333: 40pcs; UT333BT: 20pcs		
Standard carton measurement	UT333: 505mm x 330mm x 280mm; UT333BT: 332mm x 262mm x 290mm		
Standard carton gross weight	UT333: 8kg; UT333BT: 4.2kg		







UT333 BT

81