

UT333S

Digital Temperature Humidity Meter

UT333S is a stable, safe and reliable mini digital temperature humidity meter. With split type design, it is convenient to measure the temperature accurately in different environments. It is widely used in grain storage and transportation, material management, forestry and animal husbandry, healthcare, education, public sectors and home. The split type design is perfect for monitoring hard to reach places and small ventilation ducts.

- °C/°F
- MAX/MIN
- Backlight
- Data hold
- Overload alarm
- Auto power off

SPECIFICATION	Range	Resolution	Accuracy
Certificates	CE, RoHS		
Temperature	-10°C-60°C/14°F-140°F	0.1°C/0.2°F	±1°C/±2°F
Humidity	0%RH-100%RH	0.1%RH	±5%
GENERAL CHARACTERISTICS			
Power	1.5V battery (R03) x 3		
Display	32mm x 35mm		
Product net weight	310g		
Product size	110mm x 53mm x 26mm		
Standard accessories	Batteries, English manual		
Standard individual packing	Gift box, blister		
Standard quantity per carton	20pcs		
Standard carton measurement	480mm x 300mm x 360mm		
Standard carton gross weight	6.7kg		



● UT333S



UT343D

Coating Thickness Gauge

UT343D coating thickness gauge can measure coating thickness of ferrous and non-ferrous materials. This device is designed with a unique quick test feature, which allows users to set thickness range and using a 3-color LED and audio alarm to display test results, greatly increasing work efficiency. UT343D display is also auto rotatable. This CE certified device can store up to 500 sets of data for further analysis through the PC analytical software.

- LCD brightness control
- Auto rotatable screen
- Unit conversion
- Audio alarm
- LED alarm
- PC analysis software
- USB communication
- Quick test mode
- Auto power off
- Low battery indication



● UT343D

SPECIFICATION	Range
Certificates	CE, RoHS
Measurement range	0-1250um
Accuracy	±(3%+1)um
Resolution	0.1um (0-99.9um); 1um (100-1250um)
Measurement method	Single/continuous
Measurement mode	MAX/MIN/AVG
Metal type	Ferrous/ non-ferrous
Display type	2-inches TFT LCD (320 x 240 pixels)
Data storage	500 groups
GENERAL CHARACTERISTICS	
Power	3V battery (R03) x 2
Display	48mm x 36mm
Product net weight	175g
Product size	153.5mm x 64.5mm x 41mm
Standard accessories	Micro USB interface cable, calibration pieces, batteries, English manual
Standard individual packing	Gift box, cloth bag
Standard quantity per carton	10pcs
Standard carton measurement	450mm x 325mm x 255mm
Standard carton gross weight	5.9kg



- Auto-rotatable screen: 0°, 90°, 180°, 270°

- Quick test mode