

UT360 SERIES

Anemometers

UT360 series anemometers can measure temperature, wind speed, and wind count. These meters can be used in energy saving, HVAC, fishing and other industries that use exhaust or ventilation systems.

- Selectable units
- MAX/MIN mode
- LCD backlight/data hold
- Auto power off
- Low battery indication: $\leq 7.2V$
- Auto record time setup
- Wind speed display: Display "VEL"
- Wind count display: Display "FLOW"



● UT362

SPECIFICATION	Range	UT361	UT362
Certificates	CE, RoHS		
Wind speed measurement	2m/s-10m/s 10m/s-30m/s	$\pm(3\%+0.5)$ $\pm(3\%+0.8)$	$\pm(3\%+0.5)$ $\pm(3\%+0.8)$
Wind count measurement (CMM)	0.001-9999 x 100		
Wind count measurement (CFM)	0.001-9999 x 100		
Temperature measurement	0°C-40°C (32°F-104°F)	$\pm 3^\circ C (\pm 4^\circ F)$	$\pm 3^\circ C (\pm 4^\circ F)$
Display count		10000	10000
Data storage		2044	2044
USB interface			v

GENERAL CHARACTERISTICS	
Power	9V battery (6F22)
Display	57mm x 37mm
Product net weight	375g
Product size	162mm x 78mm x 30mm
Standard accessories	Battery, USB interface cable (UT362), English manual
Standard individual packing	Gift box, carrying bag
Standard quantity per carton	10pcs
Standard carton measurement	460mm x 335mm x 210mm
Standard carton gross weight	6.8kg



UT363/UT363BT

Mini Anemometers

UT363/UT363BT are mini wind speed and temperature meters. UT363 and UT363BT can measure wind speeds up to 30m/s. UT363BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and export. iENV can be downloaded from Google Play, Apple Store or UNI-T's website by searching 'iENV'.

- MAX/AVG
- Data hold
- LCD backlight
- Auto power off
- Overload indication
- Low battery indication

SPECIFICATION	UT363	UT363BT
Certificates	CE, RoHS	
Wind speed	0-30m/s	0-30m/s
Wind speed accuracy	$\pm(5\%+0.5)$	$\pm(5\%+0.5)$
Wind speed resolution	0.1m/s	0.1m/s
Temperature	-10~50°C/14~122°F	-10~50°C/14~122°F
Temperature accuracy	$\pm 2^\circ C / \pm 4^\circ F$	$\pm 2^\circ C / \pm 4^\circ F$
Temperature resolution	0.1°C/0.2°F	0.1°C/0.2°F
Wind scale	Level 0-12	Level 0-12
Wind scale accuracy	± 1	± 1
Sampling rate	0.5s	0.5s
Bluetooth APP		v

GENERAL CHARACTERISTICS	
Power	1.5V battery (R03) x 3
Display	32mm x 26mm
Product net weight	118g
Product size	160mm x 50mm x 28mm
Standard accessories	Batteries, English manual
Standard individual packing	B blister
Standard quantity per carton	UT363: 40pcs; UT363BT: 20pcs
Standard carton measurement	UT363: 505mm x 330mm x 280mm; UT363BT: 332mm x 262mm x 290mm
Standard carton gross weight	UT363: 8.42kg; UT363BT: 4.2kg



● UT363 BT