

## UT363S

### Digital Anemometer

UT363S is a stable, safe and reliable split-type anemometer, featuring quick detection, low consumption and high accuracy. It can be widely used in mining, electric, iron and steel, petrochemical, energy-saving, navigation, fan manufacturing, exhaust ventilation, sporting and more sectors.

- Overload indication
- Auto range/auto power off
- Low battery indication
- Data hold
- MAX/MIN/AVG
- Backlight
- 1m drop proof

SPECIFICATION	Range	Accuracy
Certificates	CE, RoHS	
Wind speed	0.4-30m/s	±(5%+0.5m/s)
	1.4-108km/h	±(5%+1.5km/h)
	78-5905ft/min	±(5%+100ft/min)
Temperature	0.7-58knots	±(5%+1knots)
	0.8-67mph	±(5%+1mph)
Wind scale	-10~50°C/14~122°F	±2°C/±4°F
Sampling rate	0~12	±1
Units	0.5s	
Working temperature	m/s, km/h, ft/min, knots, mph, °C/°F	
	0°C~40°C	
GENERAL CHARACTERISTICS		
Power	1.5V battery (R03) x 3	
Display	35mm x 32mm	
Product net weight	365g	
Product size	120mm x 53mm x 43mm	
Standard accessories	Batteries, English manual	
Standard individual packing	Gift box, blister	
Standard quantity per carton	20pcs	
Standard carton measurement	550mm x 295mm x 350mm	
Standard carton gross weight	7.2kg	



● UT363S

## UT370 SERIES

### Tachometers

UT370 series non-contact tachometers measure rotating speed of shaft or disk with a point laser and reflective tape on the object being measured. These meters can output RPM or count readouts without interfering with the equipment being measured.

- Data hold
- Auto power off
- Low battery indication
- MAX/MIN/AVG mode

SPECIFICATION	Range	UT371	UT372
Certificates	CE, RoHS		
RPM range	10RPM~99999RPM	±0.03	±0.03
Counts	0~99999	√	√
	Max. input frequency: 10kHz; bandwidth: 5%		
Target distance	50mm~200mm	√	√
Display count		100000	100000
USB interface			√
GENERAL CHARACTERISTICS			
Power	1.5V battery (LR6) x 4		
Display	53mm x 41mm		
Product net weight	100g		
Product size	184mm x 56mm x 34mm		
Standard accessories	Reflective tape, English manual		
Standard individual packing	Blister		
Standard quantity per carton	10pcs		
Standard carton measurement	425mm x 295mm x 180mm		
Standard carton gross weight	3.5kg		



● UT372

