

UT383S

Digital Light Meter



- Split probe
- Sampling time: 0.5s
- Auto range
- Lux/Fc selectable
- Max/Min
- Overload indication (LO/HI)
- Data hold
- Backlight
- Auto power off
- Low battery indication

Applications:

Pubic settings, light manufacturing, photo studios, interior renovation, construction, greenhouses.

SPECIFICATION	Range	Resolution	Accuracy
Certificates	CE, RoHS		
Illuminance	0~199,900Lux	1Lux (0~9999Lux)	±(4%+8)
		10Lux (≥10,000Lux)	±(5%+10)
		100Lux (≥100,000Lux)	±(5%+10)
		0.1Fc (0~999.9Fc)	±(4%+8)
		1Fc (≥1000Fc)	±(5%+10)
		10Fc (≥10,000Fc)	±(5%+10)
GENERAL CHARACTERISTICS			
Power	1.5V battery (R03) x 3		
Display	35mm x 32mm		
Product net weight	300g		
Product size	110mm x 53mm x 26mm		
Standard accessories	Batteries, English manual		
Standard individual packing	Blister, gift box		
Standard quantity per carton	20pcs		
Standard carton measurement	560mm x 300mm x 335mm		
Standard carton gross weight	6.9kg		

UT385

Laser Power Meter

UT385 Laser power meter is used to measure the energy output of laser beams for testing or laser system applications. It uses detection sensor to determine the intensity of a laser beam's energy output. It is widely used in the laboratories, teaching, medical science, industry and other fields.

- Precise laser sensor
- Split design with retractable spring wire
- LCD screen for clear readings
- Data storage function
- Selectable and customizable wavelengths
- Threshold alarm function
- Low power consumption



	ust in		
PECIFICATION	Range		
rtificates	CE, RoHS		
easurement range	0uW~39.99mW		
easurement accuracy	0uW~10uW: ±(5%+0.3); 10uW~39.9mW: ±5%		
ser wavelength range	400nm~1100nm		
ser wavelength preset options	520nm, 633nm, 650nm, 780nm		
D display	4-digit LCD display		
ampling rate	0.5s		
ata storage	199 sets		
attery level indication	√		
D backlight	√		
ıto power off	√		
perating temperature	0~40°C		
perating humidity	80%RH (no condensation)		
orage temperature	-10°C~50°C		
ENERAL CHARACTERISTICS			
ower	9V battery (6F22)		
isplay	57mm x 37mm		
oduct net weight	319g		
oduct size	198mm x 104mm x 35mm		
andard accessories	Battery, USB cable, documents download guide, English manual		
andard individual packing	Gift box, tool box		
andard quantity per carton	1pcs		
andard carton measurement	305mm x 240mm x 85mm		
tandard carton gross weight	1.24kg		



95