



UT336A REFRIGERANT LEAK DETECTOR

- Sensor: Negative Corona Sensor
- Maximum Sensitivity: 3g/a
- Warm-up Time: 3s
- Sensitivity Adjustment: 6 Levels
- Alarm Light: 6 Levels
- Battery Status
- Zero Reset
- Mute
- APO



UT681L CABLE TESTER RJ45/RJ11

- Cable Tester for RJ45/RJ11
- Fast-speed Test Mode LED1~8, LED_G
- Slow-speed Test Mode LED ~ LED*, LED_G
- Test for Short Circuit, Crossover, Open Circuit etc
- Ethernet Cable - Shielded / Unshielded
- Manual Shutdown Function
- Single Key Operation
- Low Battery Detection
- APO
- 9V Battery



UT251C HIGH SENSITIVITY LEAKAGE CURRENT CLAMP METER

- Leakage Current AC: 0.001mA ~ 600A
- Jaw capacity: 35 ~ 40mm
- Resolution: 1mA
- Auto Ranging
- Diode
- Data / Peak Hold
- Overload Protection
- Low Battery Indication
- Display 4 Digit LCD
- Data Storage 99
- Over-Range Display
- RS-232
- APO



UT503PV PV INSULATION TESTER

- Insulation Test Voltage: 125V / 250V / 500V / 1000V
- DC Voltage: 5 ~ 1000V
- AC Voltage: 5 ~ 600V
- Rated Current: 1.0mA
- Short Circuit Current: IR Measurement: < 1.5mA; PV IR Measurement: < 1.2mA
- Continue Measurement
- Compare Function
- Time Measurement
- Stepping Voltage
- Auto Discharge
- High Voltage Alarm
- DUT Live Test
- Backlight
- Data Storage 1000 Sets
- USB & Bluetooth




UT-L27 DOUBLE INSULATED TEST LEADS

- Cable Length: 900mm
- Rod Length: 130mm
- Tip Length: 16.3mm Threaded
- CAT Rating: CATIII 1000V, CATIV 600V 10A
- Safety Certificate: EN 61010-031 A1:2015
- Recommended Alligator Clips: UT-C02B
- Double Insulation UL Authenticated Material
- Removable Insulation Cap
- General Type Probes

UT-C02B - Alligator Clips

- Through Hole Alligator Clip
- Length: 80mm
- Clip Opening: 36mm
- CAT Rating: CATIII 1000V, CAT IV 600V 10A
- Insulated with M4 Threaded Bore Screw Connection
- Recommended Test Leads: UT-L13



UTD2052CL+ 50MHz STORAGE OSCILLOSCOPE

- Channels: 2 (Dual)
- Bandwidth: 50MHz
- Sample Rate: 500MS/s
- Rise Time: < 7s
- Memory Depth: 64kpts
- Waveform Capture Rate: 5000wfms/s
- Power: 100 ~ 240VAC, 50Hz/60Hz
- Vertical Scale: 1mV/div ~ 20V/div
- Time-Based Range: 5ns/div ~ 50s/div
- Storage: Setup, Wave, Bitmap
- Trigger Modes: Edge, Pulse, Alternate
- Interface USB-OTG
- Display 7 Inch TFT LCD, WVGA (400x240)

UT-CS06A 400A AC CURRENT CLAMP SENSOR

- ACA Current: 1~400A
- Jaw Opening: 28mm
- Output Ratio: 1mV/A
- True RMS
- Frequency: 50Hz ~ 400Hz
- Waveform Display: Adaptable Oscilloscope
- Suitable for Most UNI-T Multimeters



UT262E NON-CONTACT PHASE DETECTOR

- Phase Detection
- Live Power Detection
- Circuit Break Detection
- Voltage Detection
- Breakpoints Finding
- Breakpoints Positioning
- Power On Indication
- APO
- AC Voltage: 70V ~ 1000V
- Frequency: 50Hz ~ 60Hz
- Clamp Opening: 10 ~ 40mm



UT261B PHASE SEQUENCE & MOTOR ROTATION INDICATOR

- AC Voltage: 90V ~ 600V
- Frequency: 15Hz ~ 400Hz
- Working Current: < 3mA
- Phase Sequence Indication: LED
- Missing Phase Indication: LED
- Motor Rotation Indication: LED



UT586+ - DIGITAL RCD TESTER

- Test ELCB up to 550 Volts for Mining
- RCD Test Function: 10 ~ 1000mA
- Voltage: 100V ~ 440V
- Voltage Test: 30 ~ 480V
- Voltage Test: L-PE and Frequency
- Wiring Check
- Phase Angle Selection
- Lock Test
- Auto Ramp Test
- Over-temperature Detection
- Low Battery Indication
- Backlight
- APO



UT516B - INSULATION RESISTANCE TESTER

- 12KV Digital Insulation Resistance Tester
- Insulation Resistance up to 1000GΩ
- 1000V AC/DC
- Polarization Index (Pi)
- LCD Backlight
- Over-Range Warning
- Low Battery Indication
- Data Logging 18
- USB Interface
- APO
- Comparison Measurement
- 10 000 Display Count

UT345A - ULTRASONIC THICKNESS GAUGE

- Measurement Range: 1.00 ~ 300.00mm
- Sound Velocity Range: (1000 ~ 9999) m/s
- Unit: mm/in
- Lower Limit of Pipe Measurement: Ø20 x 3mm (steel)
- Data Storage: 300 groups
- Single Measurement, Continuous Measurement, Alarm, Sound Velocity Measurement, Auto Calibration
- Display: 2.4"LCD



UT285CFC DEMO - THREE PHASE POWER QUALITY ANALYSER WITH FLEX CLAMPS

- TRUE RMS Phase-to-Neutral Voltage: 1.0V~1000V
- TRUE RMS Phase-to-Phase Voltage: 1.0V~2000V
- DC Voltage: 1.0V~1000V
- TRUE RMS Current: 10mA~1000A
- Peak of Phase-to-Neutral Voltage: 1.0V~1414V
- Peak of Phase-to-Phase Voltage: 1.0V~2828V
- Current Peak: 10mA~1414A
- Active Power: 0.0VA~9999.9kW
- Reactive Power, Inductive/Capacitive: 0.0RVA~9999.9kVAR
- Apparent Power: 0.0VA~9999.9kVA
- Power Factor: -1.000~1.000
- Active Energy: 0.0Wh~9999.9MWh
- Reactive Energy, Inductive/Capacitive: 0.0VARh~9999.9MVARh
- Apparent Energy: 0.0VAh~9999.9MVAh
- Phase Angle: -179°~180°
- Tanφ: -32.76~32.76
- Phase Shift of Power Factor: -1.0~1.0
- Harmonic Ratio: 0.0%~99.9%
- Harmonic Angle: -179°~180°
- Distortion Factor: 0.0%~99.9%
- Transformer K Factor: 1.00~99.99
- 3 Phase Unbalance: 0.0%~100%
- Number of Channels: 4U / 4I
- Parameters of Electricity: W, VA, Var, PF, DPF, cosφ, tanφ
- Energy Parameters: Wh, Varh, Vah
- Harmonic: 50
- Expert Mode
- Number of Transient Records: 150Sets
- MIN / MAX
- Alarm Log
- Auto Phasor Diagram Display
- APO
- Backlight
- USB Interface



UT513A - 5KV INSULATION RESISTANCE TESTER

- 5KV Digital Insulation Resistance Tester
- Insulation Resistance up to 1000GΩ
- 600V AC/DC
- Analogue Bar Graph (30 Segments)
- Data Logging 18
- Polarization Index (Pi)
- Insulation Voltages 500/1000/2500/5000V
- Short Circuit Current < 3mA
- USB Interface
- LCD Backlight
- Over-Range Warning
- Low Battery Indication
- Secondary Display
- Dielectric Absorption (DAR)
- Auto Ranging
- High Voltage Indication
- APO
- Comparison Measurement
- 10 000 Display Count



UT1313A - 5KV INSULATION RESISTANCE TESTER

- 5KV Digital Insulation Resistance Tester
- Insulation Resistance up to 1000GΩ
- 600V AC/DC
- Analogue Bar Graph (30 Segments)
- Data Logging 18
- Polarization Index (Pi)
- Insulation Voltages 500/1000/2500/5000V
- Short Circuit Current < 3mA
- USB Interface
- LCD Backlight
- Over-Range Warning
- Low Battery Indication
- Secondary Display
- Dielectric Absorption (DAR)
- Auto Ranging
- High Voltage Indication
- APO
- Comparison Measurement
- 10 000 Display Count



a member of the **Hudaco** group

Promotion runs from 1 September 2025 to 31 December 2025 or while stocks last. Prices exclude VAT. E & OE.

Johannesburg
Tel: +27 11 392 3804

Durban
Tel: +27 31 263 7800

Cape Town
Tel: +27 21 552 5242

Email: sales@three-d.co.za

Website: www.three-d.co.za / www.uni-trend.co.za

THREE-D
AGENCIES
THE CABLE ACCESSORY COMPANY