



UT333S MINI TEMPERATURE & HUMIDITY METER (HYGROMETER)

- Temp Range: 10 ~ 60°C
- Humidity Range: 0 ~ 100%RH
- Sampling Rate 1/s
- Low Battery Indication
- LCD Backlight
- Unit Selection °C/°F
- Overload Alarm
- Data Hold
- MAX/MIN
- Power ON/OFF
- Split Design
- APO

UT665 BORESCOPE

- Pixels: 640 x 480
- Field of View: 60°
- Image Brightness: 6 levels - adjustable
- Illumination: 4 levels - adjustable
- Image Rotation
- Battery Power Indication
- Video Signal: Analog
- IP67 (Probe Only)
- Focal Length: 20mm ~ 100mm
- 4 LED Lights
- Probe Length: 1m (3m Option Available)
- Lens Dia.: 9mm
- LCD Size: 60mm
- Screen Type: TFT
- Depth Of View: >20mm



UT673PV SOLAR MPPT METER

- Max Power Measurement: 5 ~ 800W
- Max Power Current: 0 ~ 35A
- Max Power Voltage: 12 ~ 60V
- Open Circuit Current: 12 ~ 60V
- Short Circuit Current: 0 ~ 35A
- Reverse Polarity Connect Protection
- Over Voltage Protection
- Over Current Protection
- Over Temperature Protection
- Over Power Protection
- Manual / Auto MPPT Test
- Data Hold



UT593 COMPLIANCE TESTER - MULTI FUNCTIONAL

- AC Voltage: 440V
- DC Voltage: 440V
- Insulation Test: 250/500/1000V
- Phase Rotation
- Prospective Short Circuit: 26kA
- RCD Test Current: 10/30/100/300/500mA
- Low Ohm Measurement
- Loop Impedance
- ELCB Test (Time & Sensitivity)
- APO
- LCD Backlight
- Low Battery Indication
- Phase Switch (RCD) 0 ~ 180°
- Auto Half-wave Test
- 10 000 Display Count



UT312A VIBRATION TESTER

- Acceleration (PEAK): 0.1m/s²
- Velocity: 0.1mm/s
- Displacement: 0.001 ~ 1.999mm
- Automatically rotatable screen
- High/Low frequency acceleration
- Datahold
- LCD Backlight
- Battery Indication
- Flashlight
- APO
- USB C

UT377A MINI WOOD MOISTURE METER

- Wood Moisture Measurement: 2 ~ 40%
- Refresh Rate: 2 times
- Auto Range
- APO
- Low Battery Indication
- Data Hold
- MAX/MIN
- Backlight
- Ambient Temperature Correction
- 1m Drop Test
- Wood, Paper, Plywood and Other Wooden Materials



UT25CL CABLE LOCATOR

- Output Signal: 33KHz
- Energized Wire Voltage Range: AC/DC: 8~480V; AV: 50/60Hz
- Screen: Segment Mode LCD
- Signal Strength: Three Level
- Bipolar Test
- ELV LED Indicator
- Manual Sensitivity Adjustment
- Backlight
- Unipolar Test
- Flashlight



UT377C PINLESS MOISTURE METER

- Wood and Building Material Measurement: 4 ~ 99%
- Temperature Measurement: -20°C ~ 70°C
- Sensor Size: 50 x 50mm
- Minimum Target Size: 50 x 50mm
- Target Thickness Range: 6 ~ 30mm
- Screen Display: EBTN Colour Screen
- Simulation Bar Indication
- Audible Alarm Indication
- Flashlight
- APO
- Measurement mode: Softwood, Hardwood, Drywall, Masonry



UT363S MINI ANEMOMETER

- Wind Speed Rate: 0.4 ~ 30m/s
- Temperature Range: -10°C ~ 50°C
- Beaufort Wind Scale 0~12 level
- Sampling Rate 0.5/s
- Data Hold
- Split Design
- Low Battery Indication
- AVG Mode
- Wind Speed Unit Selection m/s, km/h, ft/min, knots, mph
- Temperature °C/°F
- Overload Indication
- Auto Range
- APO
- MAX/MIN
- LCD Backlight



UT373 MINI NON-CONTACT TACHOMETERS

- RPM Range: 10RPM ~ 9999RPM
- Auto Range
- Low Battery Indication
- Laser-on Indication
- Data Hold
- MAX/MIN
- Rotating Speed/Count Function Switching
- Overload Indication
- LCD Backlight
- Refresh Rate: 1s ~ 7s
- Sensor Type: Photodiode & Laser Tube
- Target Distance: 50mm ~ 200mm
- Measuring Angle: 30°
- APO



UT273+ CLAMP EARTH RESISTANCE TESTER

- Earth Resistance: 0.01Ω ~ 600Ω
- AC Current: 20A
- Jaw Size: 55mm x 32mm
- Timer
- Screen: 4 Digits EBTN Screen
- USB Cable
- Data Storage 500 sets
- Anti-Interference
- Overload Protection
- Alarm Function
- Battery state Indication
- APO



UT675A BATTERY TESTER WITH PRINTER

- 12V Battery Test: 7 ~ 16V DC
- 12V/24V Cranking System Test: 7 ~ 30V DC
- 12V/24V Charging system test: 7 ~ 30V DC
- Battery Type: Ordinary Lead Acid Battery, AGM Flat Plate Battery, AGM Spiral Battery, GEL Battery, EFB Battery
- Battery Capacity: 3 ~ 250Ah
- Over Voltage Protection
- Reverse Connection Protection
- A Prompt For Poor Contact
- Battery Status, Life and Capacity Display
- Battery Internal Resistance Display
- USB Communication
- Printing Function
- Four-Terminal Kelvin Test
- Test without Battery Disassembly
- LED Colour Indication for Test Results



UT682D WIRE TRACKER

- Wire Types: Telephone Lines/Twisted Pair/Electric Wire
- Telephone Wire Test Distance ≥3000m
- Polarity Indication for Phone Lines
- Transmitter Output Voltage: 8V DC
- Transmitter Power Supply: 9V Battery
- Receiver Power Supply: 9V Battery
- Polarity Indication for Telephone Wires
- Max Receiver Operating Current 40mA
- Max Receiver Standby Current 10mA



UT512- 1KV INSULATION RESISTANCE MULTIMETER

- 1KV Digital Insulation Resistance Tester
- Insulation Resistance up to 100GΩ
- DC Voltage: 600V
- AC Voltage: 600V
- Analogue Bar Graph (30 Segments)
- Data Logging 18
- Polarization Index (Pi)
- Dielectric Absorption (DAR)
- Insulation Voltages: 500/1000V/1500V/2500V
- Short Circuit Current < 1.8mA
- Auto Ranging
- High Voltage Indication
- Over-Range Warning
- LCD Backlight
- Low Resistance: 0.1 ~ 999.9Ω
- Low Battery Indication
- Comparison Measurement
- 10000 Display Count



UT219PV PROFESSIONAL AC/DC DIGITAL CLAMP METER

- ACA/DCA Current: 999.9A
- ACV Voltage: 1500V • DCV Voltage: 2500V
- DC mV Voltage: 999.9mV
- ACV: 999.9V • ACA: 999.9A
- ACA Flex Clamp Sensor: 3000A
- Power DC: 2500kVA
- Frequency: 5.0Hz ~ 999.9Hz
- Resistance: 99.99kΩ
- Capacitance: 1000μF
- Temperature: -40°C ~ 400°C
- True RMS • Display Count: 9999
- Jaw Opening: 35mm
- Solar Panel Polarity Indication
- High Voltage Alarm
- Over Range Indication
- Auto Hold
- Inrush Current
- APO
- Data hold
- Overload Indication
- Low Battery Indication
- PEAK
- LCD Screen
- Bluetooth
- True RMS



UTP3315TFL-II POWER SUPPLY

- Output Voltage: 0-30V
- Output Current: 0-5A
- Output Power: 150W
- Ripple Noise: ≤ 0.8mVrms
- Reliability: MTBF(e): ≥2000hrs
- Display Mode: LED Voltage and Current Dual Display



UT196 1700V DC TRUE RMS PROFESSIONAL MULTIMETER-SOLAR PRO

- AC Voltage: 1500 V
- DC Voltage: 1700 V
- Resistance: 60MΩ
- Frequency: 1MHz
- Capacitance: 60mF
- True RMS
- Dual Display • Low Pass Filter
- Auto Range • NCV
- MAX/MIN • Diode
- Continuity Buzzer
- Relative Mode • Analog Bar
- Flashlight Backlight
- Low Battery Indication
- Auto Power Off
- Display Count 6000

UT383BT MINI LIGHT METER

- Illuminance Measurement (Lux): 0 ~ 199,900 Lux
- Illuminance Measurement (FC): 0 ~ 18,500FC
- Resolution: 1 Lux, 10Lux, 100Lux, 1FC, 10FC
- Sampling Rate: 0.5/s
- Bluetooth App
- Bluetooth
- Data Hold
- APO
- Low Battery Indication
- MAX/MIN
- LCD Backlight
- Overload Indication
- Tripod Mounting Hole



excl VAT
R746.00

excl VAT
R12 699.00

excl VAT
R8 396.00

excl VAT
R635.00

excl VAT
R2 082.00

excl VAT
R1 070.00

excl VAT
R1 416.00

excl VAT
R4 096.00

excl VAT
R972.00

excl VAT
R8 719.00

excl VAT
R2 809.00

excl VAT
R2 535.00

excl VAT
R4 444.00

excl VAT
R650.00

excl VAT
R3 409.00